

MAX-AIR 35 LS-E/ACD LIGHT SERIES

Made
in Texas
U.S.A.

AIR TO GO...™ 4.2 SCFM FULLY AUTOMATIC!

The LS, light series, is the newest addition to our performance proven model #35. At only 105 lbs it comes packed with standard features, not found on any other brands, such as; All aluminum frame, intake stowing compartment, extra vibration dampening on purification, 30% more cooling, back pressure regulator, automatic pressure shut off, automatic condensate drains and much, much more. Check our standard features against the competition.



Standard Features included in base price:

- 4.2scfm** - fill an 80 cft tank in approx. 22 min.*
- Transportable @ 105lbs
- Dimensions: Electric – length 27" x depth 13¾" x height 16"
- Mounted on a enclosed, durable powder coated, **all aluminum frame** with convenient carry handle
- **OSHA compliant fan and belt guards**
- Reliable USA made electric motor with ON/OFF switches
- Oil/water separating chambers (**automatically drains**)
- Magnetic Starter, overload protection, fused transformer on 220 volt model (no transformer on 115 volt)
- **Automatic condensate drain system (A.C.D.)** see **E** above
- **Unloader timers, 2 each - with drain on shut down and preset for climate conditions**
- Air line, visual CO/moisture indicator P/N MI-4000
- **Tri-chem** breathing air purification system with active carbon/molecular sieve 13X /hopcalite
- Disposable cartridge is convenient and easy to replace (P/N LF-1001) processing capacity 2440 cu.ft @ 72° F approx. 11 hours/30 dive cylinders
- **Back pressure regulator** for optimum air processing and prolonged cycle life– see **A** above
- **Automatic/Adjustable pressure shut off** switch – see **D** above
- Final pressure relief valve
- **Hour meter** standard – see **B** above
- Oil filled pressure gauge 0–5800 psi/400 bar
- Filling hose with **On/Off valve and bleed** – see **C** above (SCUBA yoke, SCBA, DIN300 or Paintball)
- Spare parts list and owner's manual
- One year warranty

Factory Options not included in base price:

- SS-4000-35 Soft Start Package

Model # MAX-AIR 35 LS-E/ACD

Charging rate 4.2 SCFM; 3.5 F.A.D.**
(Fill time for 80 cu. ft. cyl 22 min*)
Will fill SCBA's to 4500 psi

Specifications Pumping Group***

- Construction: Air cooled, four stage, four cylinder high pressure, non-continuous duty, compressor
- ALL STAINLESS STEEL INTERSTAGE AND FINAL STAGE COOLERS**
- Max Pressure: 4800psig-330bar
 - Approx. Output: 3.5 F.A.D. 4.2 scfm charging rate**
 - Max R.P.M.: 2800
 - Lubrication: Splash lubrication with oil thrower pin
 - Oil Capacity: 12 oz.
 - Oil Type: MaxLube 501 synthetic compressor oil
 - Drive Options: AC electric motors in single or three phase 115v/230v @ 50/60 Hz (Full load amps 29/14.5) (plug not provided, consult your local electrical code)
 - Noise Level: 77 dB at 3 meters

Purification Information

Note: The #LF-1001 cartridge life is based on 72°F intake temperature, draining the condensate every 15 minutes, depending on humidity. The 2,440 cu. ft. must be de-rated by 2% for every 1°F above 72°F. The reverse applies for temperatures below 72°F.

Example: 82°F. decrease capacity by 20%.

DO NOT use where temp. could exceed 120°F

*Time required to fill an 80 cu. ft. cylinder from 500 to 3000 psig

**Based on charging an 80 cu. ft. cylinder from 500 to 3000 psig

*** Specifications and prices subject to change without notice

Breathing air quality
meets or exceeds:
NFPA 1500
CGA "E"
EN 12021
ISO 9001 : 2000
REGISTERED FIRM

 **Max-Air**®
HIGH PRESSURE BREATHING AIR COMPRESSORS

2807 Peddler Lane West • Kerrville • Texas 78028 • USA
Tel. (830) 257-5006 • Fax (830) 257-3720 • e-mail: info@max-air.com
www.max-air.com