

MAX-AIR 90 Std DY (YANMAR® DIESEL)

5000 psi
10.8 scfm

AIR TO GO...™

High pressure, breathing air compressor for SCUBA, SCBA & Paintball. Designed for economy, mobility and simplicity at an affordable price, loaded with standard features.



The Max-Air 90 Standard is a dependable, high quality, breathing air compressor designed for continuous duty at an affordable price. Heavy duty design has commercial, marine, military, dive, police, paintball and fire department applications. You will find the Max-Air 90 Standard is ideal for dive centers, pleasure boats or fixed installations.

Compare the Max-Air 90 Standard prices and features with any of the competition.

Standard Features included in base price:

- Max-Air 90 Standard – 10.8 scfm** 5000 psi
- Reliable air cooled, rope start, 10 HP Yanmar® diesel engine
- Mounted on a durable heavy duty, powder coated, steel frame
- **Adjustable engine/belt tensioning base**
- Tri-chem breathing air purification system with activated carbon/molecular sieve 13X/hopcalite
- Disposable purification cartridge is easy to replace
- Breathing air processing capacity of 10,000 cft @ 72°F or prox 18 hours run time
- New large capacity separators for Hot/Humid climates
- Manual condensate drains
- Pressure maintaining valve
- Pressure relief valve on all stages
- Intake filter
- Final pressure gauge 0~5800 psi/400 bar
- **Engine oil drain extension tube**
- **58 oz (1.7 Lt) MaxLube 501 synthetic compressor oil (1st oil change)**
- (2) filling hose with On/Off valve and Bleed (SCUBA yoke, SCBA, DIN300 or Paintball)
- **6 foot, rigid, two piece intake tube**
- Spare parts list and owner's manual
- One year warranty

Model Max-Air 90Std-DY (Weight & Dimensions Prox)
340 lbs Length 42" x Depth 20" x Height 29"
Noise level 96 dB at 3 meters

Charging rate 10.8 SCFM ; 9.0 F.A.D.**
(Fill time for 80 cu. ft. cyl 7.5 min*)
Will fill SCBA's to 4500 psi

Breathing air quality meets or exceeds:
NFPA 1500
CGA "E"
EN 12021
ISO 9001 : 2000
REGISTERED FIRM

Specifications Pumping Group***

- Construction Continuous duty, air cooled, three stage, three cylinder high pressure compressor.

ALL STAINLESS STEEL INTERSTAGE AND FINAL STAGE COOLERS.

- Max. Pressure 5000 psig – 340 bar
- Output Prox. 9.0 F.A.D.; 10.8 scfm charging rate **
- Lubrication Splash lubrication with oil thrower pin
- Oil type MaxLube 501 synthetic compressor oil
- Drive Motor Air cooled, rope start, 9 HP, Yanmar® engine

Refill time Output 10.8 scfm**; 7.5 minutes*

*Time required to fill and 80 cu. Ft. cylinder from 500 to 3000 psig

**Based on charging an 80 cu. Ft. cylinder from 500 to 3000 psig

***Specifications and prices subject to change without notice

Factory Options not included in base price:

- CD-1000 Automatic condensate drain with timers preset to drain periodically and on shut down
- AS-1001-DY+ Automatic shut down pressure switch with solenoid kit
- IS-1000 Interstage pressure gauges
- MI-4000 Air line visual Moisture/CO indicator for cartridge life
- LO-1005 Low oil shut down switch
- HT-1006 High temperature shut down switch
- ES-90-DY Electric start engine with battery recharge
- BP-12V-DY Battery package
- PU-35000 Up-grade purification capacity to 35,000 cft @ 72°F or prox 65 hours run time

+Can only be installed with ES-90-DY, BP-12V-DY unless 12 VDC power is supplied by customer

 **Max-Air®**
HIGH PRESSURE BREATHING AIR COMPRESSORS

2807 Peddler Lane West • Kerrville • Texas 78028 • USA
Tel. (830) 257-5006 • Fax (830) 257-3720 • e-mail: info@max-air.com
www.max-air.com